

CONFIGURATION

Model	UT-1325P	UT-1530P	UT-2040P	UT-3060P
Working Area	1300*2500mm	1500*3000mm	2000*4000mm	3000*6000mm
Cutting Speed	10-15m/min			0.2m-5m/min
Transmission System	1.5m rack,square 20 liner guide and slider			1.5M Gear Rack/25mm Rail Guide
Operating System	Starfire SF2100/DSP A12 control system			
Driver	JMC stepper motor and driver			Hybrid servo motor
Plasma Power Supply	Huayuan / Hypertherm			
Cutting Thickness	0-100mm			
Cutting Type	Plasma/Flame cutting/Plasma+Flame cutting			
Input Voltage	3 phase,220v/380v±10%			
Mode of file transfer	USB Interface			
Water Tank	Underlay steel sink(absorb smoke and prevent burning)			
Table-Board	sawtooth+square pipe,spacing is 70 mm			5mm Flat table+Water table
Straight line positioning precision	±0.2mm/10m			
Straight line repeat precision	±0.3mm/10m			
Environmental temperature	-5~45°C			
Humidity	<90%			
Voltage	110V/220V/380V			
Rated Power	10.5kw			

Power Consumption	10.5kWh/h	
-------------------	-----------	--